

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/39721 A1

- (51) International Patent Classification: **H04N 1/024** (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (21) International Application Number: PCT/US00/30979
- (22) International Filing Date:
10 November 2000 (10.11.2000)
- (25) Filing Language: English (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AE, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (26) Publication Language: English
- (71) Applicant: **DOCUPORT, INC.** [US/US]: 12 Spielman Road, Fairfield, NJ 07004 (US).
- (72) Inventor: **TULLI, Raja**: 1155 Rene Levesque W., Montreal, Quebec H3B 3T6 (CA).
- (74) Agent: **GILMAN, Michael, R.**, Kaplan & Gilman, L.L.P., 900 Route 9 North, Woodbridge, NJ 07095 (US).
- Published:**
with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette*

(54) Title: PORTABLE APPARATUS AND METHOD FOR READING A DOCUMENT



(57) **Abstract:** The present invention relates to a reading device (Fig. 1) for reading data on a document. It is substantially rectangular, and the length is approximately equal to the width of a standard sheet of paper. The device is readily portable because it is equipped with a clip (2), therefore it may be secured onto a shirt pocket, and as well it is equipped with a hinge assembly (9, 12), therefore it may be folded, and easily carried inside a pocket or a wallet. The invention provides a user with numerous scanning options because the device may be used in its fully open position (Fig. 5) or in its folded position (Fig. 6).

WO 02/39721 A1

PORTABLE APPARATUS AND METHOD FOR READING A DOCUMENTBACKGROUND OF THE INVENTION

5 The field of the present invention generally relates to a data reading apparatus. Prior art includes all portable, scanning devices, such as the CapShare by Hewlett-Packard. However, the present invention differs from other portable scanning devices in that a hinge assembly renders it foldable, therefore heightening its portability and utility. Multiple scanning options are available to the user because of the hinge assembly, and
10 rendering it markedly different from any other devices.

15

SUMMARY OF THE INVENTION

The present invention relates to a method and apparatus for reading media such as a document bearing text or images. The heart of the invention is a
20 readily portable device for reading documents, which may be folded by means of a hinge assembly mounted in the center of the length of the device. The hinge assembly heightens the compactness and portability of the device, and provides the user with multiple scanning position options.

25 In a preferred embodiment, a plurality of reading mechanisms are assembled in a module that is substantially rectangular. The length of the module is approximately the width of a standard sheet of paper. The reading mechanisms are positioned along the long length of the module such that the reading method comprises pressing the module across a
30 document to be read and manually moving the module in the direction desired. A clip that is closed at a superior end and open at an opposite end is attached to the module such that the clip may straddle a pocket attached to clothing. The utility of the clip mechanism is to render the module portable.

35

A hinge assembly mounted vertically in the center of the length of the device rotatably connects the halves of the module, and allows the module to be folded. The hinge assembly provides two scanning positions: one when the device is folded and the other when the device is straight. In a
40 folded position, the reading mechanisms lie parallel to each other, and in a straight position, the reading mechanisms are in a linear array. A locking device allows the module to be secured into place either when the module is folded or straight.

45 The scanner is equipped with an internal memory mechanism such that all information may be downloaded into a computer at a later time.

In another embodiment, the device is bisected obliquely, and a hinge assembly rotatably connects the halves. In a straight position, the reading mechanisms are positioned in a substantially linear array, but the angle of
50 the division causes the reading mechanisms to overlap. However, the perpendicular direction of traversing the device across a document ensures that no information is lost. In a folded position, the reading mechanisms are parallel to each other.

55

In a further embodiment, the hinge assembly is mounted across the width of the device such that in a folded position the reading mechanisms are facing each other. In a folded position, scanning occurs when a document is slid in between the reading mechanisms. Thus, double-sided scanning
60 is possible.

BRIEF DESCRIPTION OF THE DRAWINGS

65 The invention is described in more detail below with respect to an illustrative embodiment shown in the accompanying drawings in which:

Figure 1 illustrates the reading device in an open position.

70 Figure 2 illustrates the reading device in a folded position.

Figure 3 displays the reading device bisected obliquely.

Figure 4 displays the reading device bisected obliquely and folded.

75 Figure 5 depicts the reading device in an open position.

Figure 6 depicts the reading device in a folded position with the reading mechanisms facing each other.

80

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments will now be described with respect to the drawings. To facilitate description, any numeral identifying an element in
85 one figure will represent the same element in any other figure.

In a first embodiment of the present invention, **Figure 1** illustrates a foldable reading device 1. The device is substantially rectangular,
90 compact and lightweight so as to be easily manipulated by the user, and houses a plurality of reading mechanisms necessary for a contact image sensor type scanner. A clip 2 is displayed which is closed at a superior end 3, and open at an opposite end 4. The open end enables the user to straddle the light pen onto a pocket attached to clothing. Thus, the
95 reading device is easily portable and may be securely carried anywhere.

The length of the device, in its fully opened position, is approximately the width of a standard sheet of paper. A standard sheet of paper is defined as having dimensions of 8 1/2 x 11 inches, thus the device is
100 approximately 8 1/2 inches long. Therefore, in its folded position, the device is approximately half this size. The length is the largest dimension of the device and the clip lies parallel to the length. A plurality of solid state devices are arranged along the length of the device such that the entire length of a line of a page may be read and converted to a digital
105 image.

Reading occurs upon the user placing the device flat across the surface of the document to be read and manually moving it in the direction desired. The solid state elements read the full width of each line as the device is
110 traversed. The device is equipped with a battery. In that the device is a

hand-held unit, an internally disposed electrical source is required for desired operation.

115 Folding and opening the device is realized by means of a hinge assembly 5 that is mounted vertically on the device. The hinge assembly divides the module into two equal parts and rotatably connects the halves. When the device is in its fully opened position, the reading mechanisms 6 are fixed in a linear arrangement. In the fully opened position, a locking mechanism 7, serves to hold the halves together in one straight, unitary device.

120 Conversely, when the device is in its folded position, as shown in **Figure 2**, the halves are fixed alongside each other, and the reading mechanisms are positioned parallel to each other. The locking mechanism 7 secures the halves in the folded state.

125 The utility of the reading device is heightened because of the hinge assembly. The hinge assembly provides numerous scanning options and advantages for using the device. First, in its fully opened position, a user may easily scan the full width of a standard sheet of paper. Second, its
130 folded position provides the user with a simple way to scan smaller documents, such as business cards or receipts. The folded position also renders the device compact, and readily portable in a shirt pocket or wallet.

135 In another embodiment of the present invention, as illustrated in **Figure 3**, the device is bisected obliquely 8, and the halves are rotatably connected by means of a hinge assembly 9. In a fully opened position, the reading mechanisms are arranged in a substantially linear array, but the angle of the division causes the reading mechanisms 10, to overlap each other, as shown. Thus, the scan lines are parallel. However, no information is lost

140 because to scan a document the device is traversed across a document
such that the reading direction is perpendicular to the alignment of the
reading mechanisms. The data is stored in the memory, and subsequently
downloaded into a computer, where the image will be adjusted such that a
complete representation of the original image is created. A locking
145 mechanism **11** secures the halves in a straight, unitary device.

In a folded position, the reading mechanisms lie parallel to each other, as
shown in **Figure 4**, and the halves are fixed alongside each other by
means of the locking mechanism **11**.

150 In a further embodiment of the present invention, as illustrated in **Figure 5**
the hinge assembly **12** is mounted vertically on the device, rotatably
connecting the halves. A locking mechanism **13** secures the device in a
fully opened position, or in a folded position. In a fully opened position, the
155 device is fixed in a straight line, and the reading mechanisms are in a
linear array.

The hinge assembly is mounted such that in a folded position, the halves
of the device are in a parallel alignment, and the reading mechanisms face
160 each other, as illustrated in **Figure 6**. In a folded position, this arrangement
of the reading mechanisms further increases the utility of the present
invention by providing a double-sided scanning capability. It is possible for
a user to scan both sides of a document simultaneously.

165

CLAIMS

The invention has been described in detail with particular reference to
170 the preferred embodiments thereof, but it will be understood that
variations and modifications can be effected within the spirit and scope of
the invention.

I claim:

175

1. An apparatus and method for reading a document comprising;
a hinge assembly mounted vertically on a reading device such that
the halves of said device are rotatably connected;
in a folded position, the halves of the device are secured alongside
180 each other, and the reading mechanisms are parallel to each other.

180

2. An apparatus and method for reading a document, as claimed in
Claim 1 comprising;
a hinge assembly mounted vertically on a reading device such that
185 the halves of said device are rotatably connected;
reading mechanisms which overlap each other;
the direction of traversing the reading device is perpendicular to the
reading mechanisms;
in a folded position, the halves of the device are secured alongside
190 each other, and the reading mechanisms are parallel to each other.

185

190

3. An apparatus and method for reading a document, as claimed in
Claim 1 comprising;
a hinge assembly mounted vertically on a reading device such that

195 the halves of said device are rotatably connected;
in a folded position, the halves of the device are secured alongside
each other, and the reading mechanisms are facing to each other.

4. An apparatus and method for reading a document, as claimed in
200 Claim 1 comprising;
a clip that lies parallel to the scan line, comprising an open end and
a closed end such that the clip may straddle a pocket.

1/8




FIG. 1

2/8




FIG. 1a

3/8




FIG. 1b

4/8




FIG. 2

5/8




FIG. 3

6/8




FIG. 4

7/8




FIG. 5

8/8




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/30979

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H04N 1/024

US CL : 358/473

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 358/473, 474, 472, 496; 382/313

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
None

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST: folding, folded, hinge, hinged, portable, hand-held, handheld, compact, scanner or reader, document or original

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,739,923 A (KAWAHARA) 14 April 1998, Figs. 1-4, col. 2, line 36 - col. 3, line 20	1-3
X	US 5,865,431 A (MA) 02 February 1999, Figs. 1-5, col. 1, line 60 - col. 2, line 55	1-3

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"G" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

11 JANUARY 2001

Date of mailing of the international search report

22 MAR 2001

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CHEUKFAN LEE

Telephone No. (703) 305-4867